#FW

CERTIFICATE OF MAILING BY FIRST CLASS MAIL (37 CFR 1.8) Applicant(s): Uwe Liess, et al.			Docket No. 02P15832	
Application No. 10/697,331	Filing Date October 3 (2000)	Examiner Thuy V. Tran	Customer No.	Group Art Unit 2821
Invention: Device for Operating Discharge Lamps by Means of a Transformer with Four Windings, and a Corresponding Method				
I hereby certify that this Response to Notice to File Corrected Application Papers (2 pg.), Notice (2 pg.) (Identify type of correspondence)				
is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to "Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450" [37 CFR 1.8(a)] on				
November 30, 2005 (Date)				
Kenneth D. Labudda, Reg. No. 41,134				
(Typed or Printed Name of Person Mailing Correspondence)				
(Signature of Person Mailing Correspondence)				
		(Signature of Person Mail	ung Corresponaence)	
		•		
Note: Each paper must have its own certificate of mailing.				

DEC 0 2 2005 IN THE UNITED ATES PATENT AND TRADEMARK OFFICE

APPLICANT(S):

Uwe Liess, et al.

EXAMINER:

Thuy V. Tran

SERIAL NO.:

10/697,331

GROUP:

2821

FILED:

October 31, 2003

CASE NO.:

02P15832

TITLED:

Device for Operating Discharge Lamps by Means of a Transformer with

Four Windings, and a Corresponding Method

OSRAM SYLVANIA INC. 800 N. Church St.

Lake Zurich, IL 60047 November 30, 2005

RESPONSE TO NOTICE TO FILE CORRECTED APPLICATION PAPERS

Commissioner for Patents P.O. Box 1450 Alexandria, Virginia 22313-1450

Sir:

This is in response to the Notice to File Corrected Application Papers that was mailed on October 31, 2005.

Attached herein is a legible Replacement Sheet for Page 1 of the Specification, as well as a copy of the Notice to File Corrected Application Papers (along with one page attachment).

Respectfully submitted,

Uwe Liess, et al.

By:

Kenneth D. Labudda

Agent for Applicant(s) Registration No. 41,134 Phone: (847) 726-6448

Fax: (847) 726-6599





UNITED STATES PATENT AND TRADEMARK OFFICE

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Serial Number 10697331

Date Mailed 10/31/05

NOTICE TO FILE CORRECTED APPLICATION PAPERS

Notice of Allowance Mailed

This application has been accorded an Allowance Date and is being prepared for issuance. The application, however, is incomplete for the reasons below.

Applicant is given 30 days from the mail date of this Notice within which to correct the informalities indicated below. A failure to reply will result in the application being ABANDONED. This period for reply is NOT extendable under 37 CFR 1.136 (a) or (b).

Specification---Page 1 is illegible.

APPLICANT MUST SUPPLY MISSING INFORMATION WITHIN 30 DAYS OF THE MAIL DATE OF THIS NOTICE.

A copy of this notice <u>MUST</u> be returned with the reply. Please address response to Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Rori Burch USPTO

Publishing Division Fax (703) 746-6830 Fax (703) 308-6642 703-305-0333 ext.135 (V)

DEVICE FOR OPERATING DISCHARGE LAMPS BY MEANS OF A TRANSFORMER WITH FOUR WINDINGS, AND A CORRESPONDING METHOD

5

10

Field of the invention

The present invention relates to a device for at least two discharge lamps. Moreover, invention relates to a corresponding operating two discharge lamps. In particular present invention relates to electronic which such a device is integrated. Operating

15 lamps comprises in this case both their starting and their being alight.

Background of the invention

It is known to operate two discharge lamps with two 20 load circuits. In this case, the term load circuit refers to the load of a bridge that is used as an inverter to operate a discharge lamp. Each load circuit dedicated preheating arrangement for has respective lamp. Furthermore, according to the internal 25 prior art, it is possible to operate two lamps in one load circuit. Here, the primary coil of a heating transformer of a series circuit of two connected in parallel and the secondary coil of the 30 heating transformer is connected between the two lamps. Furthermore, it is possible to heat all the filaments of the lamps by transformer via secondary windings, the primary winding being situated in a section of the bridge suitable for the application.

35

It is relatively complicated to implement the load circuits in terms of circuitry, since electronic control circuits with relay or transistor switches are required for a defined, sequential starting and